


## Luminaire

Code AQ40415  
Name A.24 SOSP. BINARIO MAGNETICO + INDIRETTA 3000K 2352mm BSV

## Measurem.

Code FTS1802149  
Name A.24 SOSP. BINARIO MAGNETICO + INDIRETTA 3000K 2352mm BSV

Luminaire Flux	3049.04 lm	Luminaire Power	33.00 W	Efficacy	92.40 lm/W	Efficiency	100.00%
Lamps Flux	3049.04 lm	Maximum value	502.32 cd/klm	Position	C=50.00 G=179.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	2230 mm	Width	21 mm	Height	0 mm
Horizontal Luminous Area		0.046830 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.011329 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		08-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3049.04 lm	
LED Flux=4534,56lm LED Power=29W Eff=67% EfcLed=156lm/W EfcLum=92lm/W CCT=3000K Ra=80 SDCM=2 L70(6K)=50000h							
C.I.E.	0 0 0 0 100			D DIN 5040	--		
F UTE	1.00 T			B NBN	BZ 10		



## Luminaire

Code AQ40415  
Name A.24 SOSP. BINARIO MAGNETICO + INDIRETTA 3000K 2352mm BSV

## Measurement


Code FTS1802149  
Name A.24 SOSP. BINARIO MAGNETICO + INDIRETTA 3000K 2352mm BSV

Luminaire Flux	3049.04 lm	Luminaire Power	33.00 W	Efficacy	92.40 lm/W	Efficiency	100.00%
Lamps Flux	3049.04 lm	Maximum value	502.32 cd/klm	Position	C=50.00 G=179.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	2230 mm	Width	21 mm	Height	0 mm
Horizontal Luminous Area		0.046830 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.011329 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		08-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3049.04 lm	
LED Flux=4534,56lm LED Power=29W Eff=67% EfcLed=156lm/W EfcLum=92lm/W CCT=3000K Ra=80 SDCM=2 L70(6K)=50000h							
C.I.E.	0 0 0 0 100			D DIN 5040	--		
F UTE	1.00 T			B NBN	BZ 10		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.72	1.44	2.16	2.88	3.60	OC	1.30	2.61	3.91	5.22	6.52
OB	0.72	1.44	2.16	2.88	3.60	OD	1.30	2.61	3.91	5.22	6.52

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1531.46	1527.15	1470.75	1274.63	806.80	391.36	226.86	135.49	65.58	16.67
OB	1531.46	1527.15	1470.75	1274.63	806.80	391.36	226.86	135.49	65.58	16.67
OC	1531.46	1525.16	1473.15	1366.60	1204.43	979.27	691.35	395.96	166.50	30.53
OD	1531.46	1525.16	1473.15	1366.60	1204.43	979.27	691.35	395.96	166.50	30.53



5.00	7.20	61	23	
4.00	5.76	96	36	
3.00	4.32	170	65	
2.00	2.88	383	145	
1.00	1.44	1531	581	
H[m]	D[m]	Max lux	Med lux	Alpha=35.8°+35.8°

5.00	13.04	61	23	
4.00	10.43	96	36	
3.00	7.82	170	65	
2.00	5.22	383	145	
1.00	2.61	1531	581	
H[m]	D[m]	Max lux	Med lux	Beta=52.5°+52.5°