

## Luminaire

Code BH12901+BH16001  
 Name A.39 SHARP D+IND 1184 LB 54 400K ND BCO + COVER 2X4 OPT. LB WHITE

## Measurem.


Code FTS1900355  
 Name A.39 SHARP D+IND 1184 LB 54 400K ND BCO + COVER 2X4 OPT. LB WHITE

Luminaire Flux	4797.80 lm	Luminaire Power	53.00 W	Efficacy	90.52 lm/W	Efficiency	100.00%
Lamps Flux	4797.80 lm	Maximum value	501.04 cd/klm	Position	C=0.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002650 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4797.80 lm	


LED Flux=5957,9lm LED Power=44W Eff=81% EfcLed=135lm/W EfcLum=91lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 97 99 100 36 100  
 F UTE --

D DIN 5040  
 B NBN  
 D62  
 BZ 1



ULOR 64.37 %  
 DLOR 35.63 %  
 RN 64.37 %



## Luminaire

Code BH12901+BH16001  
Name A.39 SHARP D+IND 1184 LB 54 400K ND BCO + COVER 2X4 OPT. LB WHITE

## Measur.

Code FTS1900355  
Name A.39 SHARP D+IND 1184 LB 54 400K ND BCO + COVER 2X4 OPT. LB WHITE

Luminaire Flux	4797.80 lm	Luminaire Power	53.00 W	Efficacy	90.52 lm/W	Efficiency	100.00%
Lamps Flux	4797.80 lm	Maximum value	501.04 cd/klm	Position	C=0.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area	0.010952 m2			Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°	0.002650 m2		
Coordinate system	CG			Symmetry Type	Double Symmetrical		
Date	17-07-2017			Maximum Gamma Angle	180		
Measurement Distance	0.00			Measurement Flux	4797.80 lm		


LED Flux=5957,9lm LED Power=44W Eff=81% EfcLed=135lm/W EfcLum=91lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E.	97 99 100 36 100		D DIN 5040	D62
F UTE	--		B NBN	BZ 1

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.45	OC	0.49	0.98	1.47	1.96	2.45
OB	0.49	0.98	1.47	1.96	2.45	OD	0.49	0.98	1.47	1.96	2.45

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2403.90	2386.75	2172.59	1446.30	265.03	46.07	10.79	6.90	4.53	1.69
OB	2403.90	2386.75	2172.59	1446.30	265.03	46.07	10.79	6.90	4.53	1.69
OC	2403.90	2386.75	2172.59	1446.30	265.03	46.07	10.79	6.90	4.53	1.69
OD	2403.90	2386.75	2172.59	1446.30	265.03	46.07	10.79	6.90	4.53	1.69



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0 Max non a G
1.00	0.98	2404	1447		
2.00	1.96	601	362		
3.00	2.94	267	161		
4.00	3.91	150	90		
5.00	4.89	96	58		

H[m]	D[m]	Max lux	Med lux	Beta=26.1°+26.1°	G=0.0 Max non a G
1.00	0.98	2404	1447		
2.00	1.96	601	362		
3.00	2.94	267	161		
4.00	3.91	150	90		
5.00	4.89	96	58		