

## Luminaire

Code BH14501+BH16204  
 Name A.39 SHARP D+IND 2368 LB 34 400K ND BCO + COVER 4X4 OPT. LB BLACK

## Measurem.

Code FTS1900205  
 Name A.39 SHARP D+IND 2368 LB 34 400K ND BCO + COVER 4X4 OPT. LB BLACK

Luminaire Flux	9437.68 lm	Luminaire Power	104.00 W	Efficacy	90.75 lm/W	Efficiency	100.00%
Lamps Flux	9437.68 lm	Maximum value	908.98 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area	0.021904 m2			Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°	0.005299 m2		
Coordinate system	CG	Symmetry Type	Double Symmetrical				
Date	16-02-2017	Maximum Gamma Angle	180				
Measurement Distance	0.00	Measurement Flux	9437.68 lm				
LED Flux=11915,8lm LED Power=95W Eff=79% EfcLed=125lm/W EfcLum=91lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99 100 100 35 100	D DIN 5040	D62				
F UTE	--	B NBN	BZ 1				



