

## Luminaire

Code BH14904+BH16201  
 Name A.39 SHARP D+IND 2368 LB 54 400K ND NRO + COVER 4X4 OPT. LB WHITE

## Measurem.

Code FTS1900500  
 Name A.39 SHARP D+IND 2368 LB 54 400K ND NRO + COVER 4X4 OPT. LB WHITE

Luminaire Flux	9595.60 lm	Luminaire Power	104.00 W	Efficacy	92.27 lm/W	Efficiency	100.00%
Lamps Flux	9595.60 lm	Maximum value	501.04 cd/klm	Position	C=0.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		9595.60 lm	
LED Flux=11915,8lm LED Power=95W Eff=81% EfcLed=125lm/W EfcLum=92lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	97 99 100 36 100			D DIN 5040		D62	
F UTE	--			B NBN		BZ 1	



