

## Luminaire

Code BH10405+BH16304  
 Name A.39 SHARP D+IND 2368 HB 34 300K ND SIL + COVER 6X4 OPT. HB BLACK

## Measurem.

Code FTS1900261  
 Name A.39 SHARP D+IND 2368 HB 34 300K ND SIL + COVER 6X4 OPT. HB BLACK

Luminaire Flux	10482.58 lm	Luminaire Power	125.00 W	Efficacy	83.86 lm/W	Efficiency	100.00%
Lamps Flux	10482.58 lm	Maximum value	1147.06 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area	0.032856 m2			Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°			0.007949 m2
Coordinate system	CG			Symmetry Type			Double Symmetrical
Date	16-02-2017			Maximum Gamma Angle			180
Measurement Distance	0.00			Measurement Flux			10482.58 lm

LED Flux=13475,65lm LED Power=103W Eff=78% EfcLed=131lm/W EfcLum=84lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 99 100 100 44 100  
 F UTE --

D DIN 5040  
 B NBN

C62  
 BZ 1



