


Luminaire

Code BH10701+BH16301
 Name A.39 SHARP D+IND 2368 HB 34 400K DM BCO + COVER 6X4 OPT. HB WHITE

Measurem.

Code FTS1900568
 Name A.39 SHARP D+IND 2368 HB 34 400K DM BCO + COVER 6X4 OPT. HB WHITE

Luminaire Flux	11128.86 lm	Luminaire Power	120.00 W	Efficacy	92.74 lm/W	Efficiency	100.00%
Lamps Flux	11128.86 lm	Maximum value	1143.88 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area	0.032856 m2			Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°			0.007949 m2
Coordinate system	CG			Symmetry Type			Double Symmetrical
Date	16-02-2017			Maximum Gamma Angle			180
Measurement Distance	0.00			Measurement Flux			11128.86 lm
LED Flux=14244,9lm LED Power=103W Eff=78% EfcLed=138lm/W EfcLum=93lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	97 99 100 44 100			D DIN 5040		C62	
F UTE	--			B NBN		BZ 1	



Luminaire

Code BH10701+BH16301
Name A.39 SHARP D+IND 2368 HB 34 400K DM BCO + COVER 6X4 OPT. HB WHITE

Measurerm.


Code FTS1900568
Name A.39 SHARP D+IND 2368 HB 34 400K DM BCO + COVER 6X4 OPT. HB WHITE

Luminaire Flux	11128.86 lm	Luminaire Power	120.00 W	Efficacy	92.74 lm/W	Efficiency	100.00%
Lamps Flux	11128.86 lm	Maximum value	1143.88 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		11128.86 lm	
LED Flux=14244,9lm LED Power=103W Eff=78% EfcLed=138lm/W EfcLum=93lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	97 99 100 44 100			D DIN 5040		C62	
F UTE	--			B NBN		BZ 1	

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.33	0.66	0.98	1.31	1.64	OC	0.33	0.66	0.98	1.31	1.64
OB	0.33	0.66	0.98	1.31	1.64	OD	0.33	0.66	0.98	1.31	1.64

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	12730.07	11841.33	7832.31	2816.83	497.06	117.25	30.43	16.44	10.63	4.16
OB	12730.07	11841.33	7832.31	2816.83	497.06	117.25	30.43	16.44	10.63	4.16
OC	12730.07	11841.33	7832.31	2816.83	497.06	117.25	30.43	16.44	10.63	4.16
OD	12730.07	11841.33	7832.31	2816.83	497.06	117.25	30.43	16.44	10.63	4.16



H[m]	D[m]	Max lux	Med lux	Alpha=18.1°+18.1°	G=0.0
1.00	0.66	12730	7395		
2.00	1.31	3183	1849		
3.00	1.97	1414	822		
4.00	2.62	796	462		
5.00	3.28	509	296		

H[m]	D[m]	Max lux	Med lux	Beta=18.1°+18.1°	G=0.0
1.00	0.66	12730	7395		
2.00	1.31	3183	1849		
3.00	1.97	1414	822		
4.00	2.62	796	462		
5.00	3.28	509	296		