

Luminaire

Code AQ40704
Name A.24 SOSP.BIN.MAG.+IND.2700K 2352mm BLK

Measurerm.

Code FTS1801939
Name A.24 SOSP.BIN.MAG.+IND.2700K 2352mm BLK

Luminaire Flux	3003.53 lm	Luminaire Power	33.00 W	Efficacy	91.02 lm/W	Efficiency	100.00%
Lamps Flux	3003.53 lm	Maximum value	502.32 cd/klm	Position	C=50.00 G=179.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	2230 mm	Width	21 mm	Height	0 mm
Horizontal Luminous Area		0.046830 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.011329 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		08-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3003.53 lm	

LED Flux=4466,88lm LED Power=29W Eff=67% EfcLed=154lm/W EfcLum=91lm/W CCT=2700K Ra=80 SDCM=2 L70(6K)=50000h

C.I.E. 0 0 0 0 100
F UTE 1.00 T

D DIN 5040 --
B NBN BZ 10


2352mm x 27mm



Semipiani C

180.0 ——— 0.0
270.0 - - - - - 90.0

ULOR 99.98 %
DLOR 0.02 %
RN 99.98 %



Luminaire

Code AQ40704
Name A.24 SOSP.BIN.MAG.+IND.2700K 2352mm BLK

Measurerm.


Code FTS1801939
Name A.24 SOSP.BIN.MAG.+IND.2700K 2352mm BLK

Luminaire Flux	3003.53 lm	Luminaire Power	33.00 W	Efficacy	91.02 lm/W	Efficiency	100.00%
Lamps Flux	3003.53 lm	Maximum value	502.32 cd/klm	Position	C=50.00 G=179.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	2230 mm	Width	21 mm	Height	0 mm
Horizontal Luminous Area		0.046830 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.011329 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		08-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3003.53 lm	
LED Flux=4466,88lm LED Power=29W Eff=67% EfcLed=154lm/W EfcLum=91lm/W CCT=2700K Ra=80 SDCM=2 L70(6K)=50000h							
C.I.E.	0 0 0 0 100			D DIN 5040	--		
F UTE	1.00 T			B NBN	BZ 10		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.72	1.44	2.16	2.88	3.60	OC	1.30	2.61	3.91	5.22	6.52
OB	0.72	1.44	2.16	2.88	3.60	OD	1.30	2.61	3.91	5.22	6.52

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1508.60	1504.35	1448.80	1255.61	794.76	385.51	223.47	133.47	64.60	16.43
OB	1508.60	1504.35	1448.80	1255.61	794.76	385.51	223.47	133.47	64.60	16.43
OC	1508.60	1502.39	1451.16	1346.21	1186.45	964.65	681.03	390.05	164.02	30.07
OD	1508.60	1502.39	1451.16	1346.21	1186.45	964.65	681.03	390.05	164.02	30.07



5.00	7.20	60	23	
4.00	5.76	94	36	
3.00	4.32	168	64	
2.00	2.88	377	143	
1.00	1.44	1509	572	
H[m]	D[m]	Max lux	Med lux	Alpha=35.8°+35.8° G=0.0

5.00	13.04	60	23	
4.00	10.43	94	36	
3.00	7.82	168	64	
2.00	5.22	377	143	
1.00	2.61	1509	572	
H[m]	D[m]	Max lux	Med lux	Beta=52.5°+52.5° G=0.0