


Luminaire

Code 2102C10A
Name AoL SYSTEM S LIN.60 SLAVE INTERM 3500K

Measurem.

Code FTS1902577
Name AoL SYSTEM S LIN.60 SLAVE INTERM 3500K

Luminaire Flux	992.34 lm	Luminaire Power	11.00 W	Efficacy	90.21 lm/W	Efficiency	100.00%
Lamps Flux	992.34 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical
Rectangular Luminaire		Length	580 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	580 mm	Width	50 mm	Height	49 mm
Horizontal Luminous Area		0.029000 m ²		Emitting area on Plane 180°		0.029000 m ²	
Emitting area on Plane 0°		0.029000 m ²		Emitting area on Plane 270°		0.002500 m ²	
Emitting area on Plane 90°		0.002500 m ²		Glare area at 76°		0.035154 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		05-09-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		992.34 lm	
LED Flux=1244lm LED Power=11W Eff=80% EfcLed=113lm/W EfcLum=90lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	33 60 82 69 100			D DIN 5040		B21	
F UTE	0.69 H + 0.31 T			B NBN		BZ 6	



Luminaire

Code 2102C10A
 Name AoL SYSTEM S LIN.60 SLAVE INTERM 3500K

Measur.

Code FTS1902577
 Name AoL SYSTEM S LIN.60 SLAVE INTERM 3500K

Luminaire Flux	992.34 lm	Luminaire Power	11.00 W	Efficacy	90.21 lm/W	Efficiency	100.00%
Lamps Flux	992.34 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical
Rectangular Luminaire		Length	580 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	580 mm	Width	50 mm	Height	49 mm
Horizontal Luminous Area		0.029000 m2		Emitting area on Plane 180°		0.029000 m2	
Emitting area on Plane 0°		0.029000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.035154 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		05-09-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		992.34 lm	
LED Flux=1244lm LED Power=11W Eff=80% EfcLed=113lm/W EfcLum=90lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	33 60 82 69 100			D DIN 5040	B21		
F UTE	0.69 H + 0.31 T			B NBN	BZ 6		

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8