


Luminaire

Code AQ65520
Name A.24 PLF SA360 1500 SHARP FL2700 BBZ

Measurem.

Code FTS1901672
Name A.24 PLF SA360 1500 SHARP FL2700 BBZ

Luminaire Flux	6112.48 lm	Luminaire Power	83.00 W	Efficacy	73.64 lm/W	Efficiency	100.00%
Lamps Flux	6112.48 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Round Luminaire Round Luminous Area	Diam. 1550 mm Diam. 124 mm	Height	54 mm	Height	0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.012076 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.002922 m2				
Coordinate system	CG	Symmetry Type	Double Symmetrical				
Date	21-11-2018	Maximum Gamma Angle	180				
Measurement Distance	0.00	Measurement Flux	6112.48 lm				
LED Flux=7509.2lm LED Power=76W Eff=81% EfcLed=99lm/W EfcLum=74lm/W CCT=2700K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	98 100 100 100 100	D DIN 5040	A60				
F UTE	--	B NBN	BZ 1				



Luminaire

Code AQ65520
Name A.24 PLF SA360 1500 SHARP FL2700 BBZ

Measurement


Code FTS1901672
Name A.24 PLF SA360 1500 SHARP FL2700 BBZ

Luminaire Flux	6112.48 lm	Luminaire Power	83.00 W	Efficacy	73.64 lm/W	Efficiency	100.00%
Lamps Flux	6112.48 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Round Luminaire		Diam.	1550 mm	Height	54 mm		
Round Luminous Area		Diam.	124 mm	Height	0 mm		
Horizontal Luminous Area	0.012076 m2			Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°		0.002922 m2	
Coordinate system	CG			Symmetry Type		Double Symmetrical	
Date	21-11-2018			Maximum Gamma Angle		180	
Measurement Distance	0.00			Measurement Flux		6112.48 lm	
LED Flux=7509.2lm LED Power=76W Eff=81% EfcLed=99lm/W EfcLum=74lm/W CCT=2700K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	98 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.24	0.47	0.71	0.95	1.18	OC	0.25	0.50	0.75	1.00	1.25
OB	0.24	0.47	0.71	0.95	1.18	OD	0.25	0.50	0.75	1.00	1.25

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	17018.02	15448.24	7156.70	2864.32	1624.47	40.71	14.12	4.04	0.00	0.00
OB	17018.02	15448.24	7156.70	2864.32	1624.47	40.71	14.12	4.04	0.00	0.00
OC	17018.02	16081.07	7805.27	3096.71	1604.69	59.39	16.32	3.87	0.00	0.00
OD	17018.02	16081.07	7805.27	3096.71	1604.69	59.39	16.32	3.87	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=13.3°+13.3°	G=0.0 Max non a G
1.00	0.47	17188	10611		
2.00	0.95	4297	2653		
3.00	1.42	1910	1179		
4.00	1.89	1074	663		
5.00	2.37	688	424		

H[m]	D[m]	Max lux	Med lux	Beta=14.1°+14.1°	G=0.0 Max non a G
1.00	0.50	17188	10611		
2.00	1.00	4297	2653		
3.00	1.50	1910	1179		
4.00	2.01	1074	663		
5.00	2.51	688	424		