

Luminaire

Code AQ64204APP
 Name A.24 PLF SA360 1122 SHRP FL3000K BK APP*

Measuram.

Code FTS2000019
 Name A.24 PLF SA360 1122 SHRP FL3000K BK APP*

Luminaire Flux	3256.16 lm	Luminaire Power	42.00 W	Efficacy	77.53 lm/W	Efficiency	100.00%
Lamps Flux	3256.16 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Round Luminaire Round Luminous Area	Diam. 1122 mm Diam. 88 mm	Height	54 mm	Height	0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.006082 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°			0.000000 m2 0.000000 m2 0.001471 m2		
Coordinate system	CG	Symmetry Type			Double Symmetrical		
Date	21-11-2018	Maximum Gamma Angle			180		
Measurement Distance	0.00	Measurement Flux			3256.16 lm		
LED Flux=4000.2lm LED Power=38W Eff=81% EfcLed=105lm/W EfcLum=78lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	98 100 100 100 100	D DIN 5040			A60		
F UTE	--	B NBN			BZ 1		



